



DATE: Oct 21, 2025
QUOTE #:372464-01

CITY OF LAREDO PUBLIC UTILITIES
PO BOX 210
LAREDO, TEXAS 78042-0210

Rueda, Marco
210.630.8948

Ron Miller

**BUY BOARD QUOTE
CONTRACT #685-22**

One (1) New Caterpillar Inc Model: 305 CR Compact Construction Equipment with all standard equipment in addition to the additional specifications listed below:

STOCK NUMBER: HLK049231 SERIAL NUMBER: 05G509564 YEAR: 2025 HOURS: 3

SALE PRICE	\$72,317.05
EXT WARRANTY	Included
CSA	Included
TOTAL PRICE	\$72,317.05
SUB TOTAL	\$72,317.05
HET (0.181%)	\$130.89
TOTAL TAXES	\$130.89
TOTAL PURCHASE PRICE	\$72,447.94

WARRANTY

Standard Warranty: 24 Month/2000 Hour Total Machine Limited Warranty
Extended Warranty: 305-36 MO/2000 HR POWERTRAIN + HYDRAULICS
CSA 500 & 1000HR PM Parts Only Kits (Maintenance parts only kits, excludes fluids)

MACHINE SPECIFICATIONS

STOCK NUMBER: HLK049231 SERIAL NUMBER: 05G509564 YEAR: 2025 HOURS: 3

DESCRIPTION	REF.#
305 07A CR MHE DCA1C	661-0399
BELT, SEAT, 3" RETRACTABLE	510-6085
BELT AS-SEAT	595-1980
BOOM, SWING	527-7599
LINES, BOOM	527-7611
TRACK, 16", RUBBER BELT	527-7627
FILM, INC. CANADA	552-5984

DESCRIPTION	REF.#
SOFTWARE, PROPORTIONAL CONTROL	557-1709
SOFTWARE, STICK STEER CONTROL	557-1710
SOFTWARE, 2 WAY CONTROL	557-1711
SOFTWARE, CODED START	557-1713
305 07A CR MINI EXCAVATOR	576-7009
COUNTERWEIGHT, STANDARD	576-9149
CANOPY, ROPS	578-1749
MONITOR NEXT GEN, NO CAMERA	579-2595
ALARM, TRAVEL	579-8852
ELECTRICAL ARR, C1.7 HRC	579-8859
LIGHTS, LED	579-8868
LINES, STICK	584-3653
LINKAGE BUCKET W/LIFTING EYE	584-4306
CONTROL, QC, 3 LINE	584-4311
LINES, QC, LNG STK, 3 LINE	586-0416
INSTRUCTIONS, ANSI	595-7021
HYDRAULIC OIL	595-9905
STICK, LONG, WITH 1ST AUX	596-7594
BLADE, STD, BOCE	597-0753
ENGINE, EPA TIER 4 FINAL	611-2417
CAT KEY, WITH PASS CODE OPTION	660-4095
SHIPPING/STORAGE PROTECTION	0P-2266
PACKING, LAST MILE PROGRAM	0P-4299
PRODUCT LINK, CELLULAR PL243	628-8009
LANE 2 ORDER	0P-9002
SERIALIZED TECHNICAL MEDIA KIT	421-8926
BUCKET - 5G509564B	464-9911

STANDARD EQUIPMENT

POWERTRAIN

Cat C1.7T diesel engine
 -U.S. EPA tier 4 final
 -EU stage V
 -ISO 9249/EEC 80/1270
 -Rated net power 34.1kW
 -2,400 rpm - ISO 9249/EEC 80/1269
 -Electronic engine, turbo, DOC (diesel oxidation catalyst)

Automatic engine idle
 Automatic engine shut-off
 Automatic swing brake
 Automatic two speed travel
 Fuel and water separator with indicator
 Radial seal, double element air filter
 with restrictions indicator

HYDRAULICS

Smart tech electronic pump
 Variable displacement piston pump
 Load sensing & flow sharing hydraulics

Power on demand
 Hydraulic temperature monitoring
 Accumulator - certified

ELECTRICAL

12 volt electrical system

Ignition key stop switch

85 ampere alternator
650 CCA maintenance free battery
Battery disconnect
Circuit breaker

Signalling/warning horn
Work lights
-Cab, boom left
-Courtesy safety light

OPERATOR ENVIRONMENT

Sealed and pressurized unitized cab
Operator sound pressure 72 dB(A) ISO6396
Integrated lower front window
Rear window emergency exit
Radio - bluetooth, USB, aux, mic
12V power socket
Ergonomic joystick control levers
Adjustable wrist rests
Pattern changer
Color LCD monitor
-Fuel level, coolant temperature and warning indicator
-Maintenance and machine monitoring
-Performance & machine adjustments
-Numeric security code

-Multiple languages
-Hour meter
-Jog dial control interface
Coat hook
Cup holder
Hydraulic lockout controls
Literature holder
Molded footrests
Removable washable floormat
Retractable fluorescent "high visibility" seat belt
Travel control pedals with hand levers
Utility space for mobile phone skylight
mounting bosses for top & front guards

FLUIDS

Extended life coolant - 37C

Hydro advanced hydraulic oil

OTHER STANDARD EQUIPMENT

Cat key with passcode option
Locks on external enclosure doors
Lockable fuel cap
Beacon socket
Ecology drain - engine oil
Side by side engine & hydraulic oil cooler
Stick steer mode
Cruise control mode
Power on demand
Rear reflectors

Roll-over protective structure (ROPS) (ISO 12117-2)
Product Link PL243 (regulations apply)
Auxiliary hydraulic lines
-1-way and 2-way (combined function)
-Auxiliary line quick disconnects
-Adjustable auxiliary flow
-Continuous flow
-Adjustable auxiliary relief
Thumb ready stick