



 * Illustration purposes only. Actual dimensions and specs subject to accepted quote. *

\$77,320.41

P6 - 5(H) X 10(W) with Trailer Double sided

Quote valid until Saturday, June 8, 2024

Genoptic Smart Display Sales Quote

Laredo Police

Homar Soli

hsolis@ci.laredo.tx.us

Quote Type: Deale

Currency: USD

Reference: 197f1081-0f41-4230-9aba-

4ab458044723

Prepared: Thursday, May 9, 2024

Quote Expiry: Saturday, June 8, 2024

P6 - 5(H) X 10(W) Double sided

- Trailer
- 2 Honda EU7000 Generators
- Cell Modem

\$77,320.41

- * Wireless communication devices, including but not limited to RF Modems and Wireless Ethernet, offered by Genoptic Smart Displays may be affected by site specific conditions that can hinder the performance or operation of said devices. Genoptic Smart Displays makes no guarantees written or verbally, that the communication device is suitable for a particular project or location. Selection, purchase and acceptance of the chosen communication device is at the sole discretion of the purchaser.
- ** Lead Time committed is based on the date deposit is received by Genoptic Smart Displays. Lead time is not based on the date this Sales Quote was signed or returned unless otherwise noted or strictly approved in writing by Genoptic Smart Displays.
- *** The specifications contain in this quotation does NOT include support structure, installation, and electrical service to sign, cable, shipping, permits, or taxes. Cabinet dimensions are approximate. The freight charge is an approximate estimate for your reference; the actual charge may vary. Safety factor is not included. Please request electrical drawings for exact dimension and number of circuit breakers.

Specifications and Features

Specifications

- ⊘ Total Pixels: 96800
- O Pitch: 6mm High Definition
- **⊘** Software (version): LED VideoStar
- **⊘** Color Display: Vibrant Color Display
- O Cabinet: Double sided
- O Cabinet Opening: Front Module
- **⊘** Cabinet Style: Borderless
- Weight (lbs.): 554.400 (277.200 per side)
- Wattage: Max watts 6250 / (3125 per side) / Average watts 2200
- (1100 per side)

Features

- ② IP68 Rating: Backed by an international standard rating of IP68 means our signs are deemed fit enough to withstand dust, dirt and sand, and are resistant to submersion up to a maximum depth of 1.5m underwater for up to thirty minutes.
- O Display Palette: Full Color
- **⊘** Colors: 281 Trillion Colors

- Graphic: Slideshow playback with fast transitions at 75 frames per second (FPS). Animation video, image and text capabale. Full live video capable.
- Ø Brightness (nits)(CD/m²): 7000

5/9/24, 4:14 PM

VideoStar Software

After years of extensive software engineering, Genoptic Smart Displays is proud to provide our proprietary VideoStar software. We have developed a more versatile user friendly software application for any type of user making it quick and easy to upload eye catching vibrant media content to one or multiple LED displays. We have also integrated our InteLED Reporting Technology which can automatically send scheduling, proof of play, performance and error message reports to your or your clients.

∅ 100% uptime and perfect for advertising	O Calculula and assessed through in this case in the
	 Schedule and groups through inutitive user interface
<u>-</u>	 Determine average dwell time using an IP camera
O Upload hundreds of media files in one click	
	Widnition your signs remotely
o supposition our common media line types	
	O Control simple or multiple displays
Advanced user account management	
O Maraneed aser decount management	

Simple and easy to use software for any application