



DATE: Oct 21, 2025
QUOTE #:362487-02

CITY OF LAREDO PUBLIC UTILITIES
PO BOX 210
LAREDO, TEXAS 78042-0210

Rueda, Marco
210.630.8948

Ron Miller

BUY BOARD QUOTE CONTRACT #685-22

One (1) New Caterpillar Inc Model: CS12-BR Paving and Compaction with all standard equipment in addition to the additional specifications listed below:

SALE PRICE	\$237,449.03
EXT WARRANTY	Included
TOTAL PRICE	\$237,449.03
SUB TOTAL	\$237,449.03
TOTAL PURCHASE PRICE	\$237,449.03

WARRANTY

Standard Warranty: 12 Month/Unlimited Hours Total Machine
Extended Warranty: CS12-12 MO/8760 HR POWERTRAIN, CS12-36 MO/3000 HR POWERTRAIN + HYDRAULICS + TECH

MACHINE SPECIFICATIONS

DESCRIPTION	REF.#
CS12 03A VIB COMP	633-8505
LANE 2 - AVAILABLE FROM PIRACICABA FACTORY	
LANE 3 - AVAILABLE FROM PIRACICABA FACTORY	
AVAILABLE FOR: ADSM-N and Puerto Rico	
NOTE: This meets U.S. EPA Tier 4 Final & EU Stage V emission	
standards and is available to ADSM-N & Puerto Rico dealers.	
SHELL KIT, SQR, PADFOOT, FLD	416-1351
LANE 3 ORDER	0P-9003
ENGINE, CAT C4.4	629-8332
FUEL SYSTEM, DOOR	577-7672
LIGHTS, LED, STANDARD	648-9429
PLATFORM, ROPS/FOPS	648-6368
SEAT, VINYL	356-1226

DESCRIPTION	REF.#
SEAT BELT, 2"	590-3401
PRODUCT LINK, CELLULAR PL641	454-5454
INSTALLATION, ROPS/FOPS	454-0250
SENSOR, DRIVE POWER (MDP)	441-6675
TIRES, 23.1-26 8PR R-3	203-4717
FREQUENCY, VARIABLE	355-3546
SCRAPER, SHELL KIT READY	472-2057
NO BLADE	357-6261
OIL, HYD, STANDARD	362-4940
FUEL ANTIFREEZE, -25C (-13F)	0P-3978
PROTECTION, CYLINDER ROD	0P-3940
STORAGE PROTECTION	0P-4782
INSTRUCTIONS, ANSI	599-6402
INSTRUCTIONS, ANSI	648-7051
SERIALIZED TECHNICAL MEDIA KIT	421-8926
FILM GP "MADE IN BRAZIL"	554-1057
LIGHTING, WARNING	355-3059
MIRRORS, REARVIEW, EXTERNAL	354-5413
GUARD, TRANSMISSION	355-2660
ROLL ON-ROLL OFF	0P-4505

STANDARD EQUIPMENT

POWERTRAIN

CAT C4.4 turbo- charged diesel engine
with glow-plug
heater
Dual element air cleaner
Fuel filter/water separator/electronic
priming pump and water indicator
Three-speed throttle switch including

ECOMODE
Dual propel pumps - 1 for drum and
1 for tires
Dual braking systems (service &
parking, drum only)
Two-speed hydrostatic transmission
Limited slip differential

ELECTRICAL

24-volt starting and charging system
alternator
(2) Maintenance free batteries -
750 CCA
Halogen working lights - canopy mounted

(2 front-facing and 2 rear-facing)
Backup alarm and forward warning horn
Product link ready
Beacon ready

OPERATOR ENVIRONMENT

ROPS/FOPS platform
Four heavy-duty isolation mounts
Platform handrails/guardrails
Power steering
Adjustable tilt-steering column
Adjustable, rotating suspension seat
Retractable seat belt
Rear view camera with display

-engine oil pressure gauge
-engine coolant temperature gauge
-alternator charge
-fuel level gauge
-service hour meter
-engine RPM
-ground speed, vibe speed
-fuel rate gauge

Adjustable, padded arm rest for
propel lever operation
On-board display with audible
warning alarm and interface for:
-hydraulic oil temperature gauge

-engine load gauge
-basic compaction measurement
Lockable, vandalism guard for
on-board display
12-volt power point

COOLING

Premixed 50% concentration of extended
life coolant with freeze protection

to -37C (-35F)

DRUMS

Smooth drum
2134 mm (84") wide x 1534 mm (60.4")
diameter
Dual amplitude with single frequency

Dual, pod-style eccentric weight
 housings
Front adjustable steel scraper

OTHER STANDARD EQUIPMENT

Locking composite engine enclosure
Sealed-for-life hitch bearings
Sight gauges:
-coolant level
-hydraulic oil level
Hydraulic tank locking cap
Articulated frame with safety lock
Transport tie-down and lift points

Fuel tank with lockable cap
Quick connect hydraulic pressure test
ports
SOS ports:
-engine
-hydraulic
-coolant
Universal bumper