

DATE: Oct 21, 2025 QUOTE #:362487-02

## **CITY OF LAREDO PUBLIC UTILITIES**

PO BOX 210 LAREDO, TEXAS 78042-0210 **Rueda, Marco** 210.630.8948

## **Ron Miller**

# **BUY BOARD QUOTE CONTRACT #685-22**

One (1) New Caterpillar Inc Model: CS12-BR Paving and Compaction with all standard equipment in addition to the additional specifications listed below:

SALE PRICE	\$237,449.03
EXT WARRANTY	Included
TOTAL PRICE	\$237,449.03
SUB TOTAL	\$237,449.03
TOTAL PURCHASE PRICE	\$237,449.03

## **WARRANTY**

Standard Warranty: 12 Month/Unlimited Hours Total Machine

Extended Warranty: CS12-12 MO/8760 HR POWERTRAIN, CS12-36 MO/3000 HR POWERTRAIN + HYDRAULICS +

**TECH** 

#### **MACHINE SPECIFICATIONS**

DESCRIPTION	REF.#
CS12 03A VIB COMP	633-8505
ANE 2 - AVAILABLE FROM PIRACICABA FACTORY	
ANE 3 - AVAILABLE FROM PIRACICABA FACTORY	
AVAILABLE FOR: ADSM-N and Puerto Rico	
NOTE: This meets U.S. EPA Tier 4 Final & EU Stage V emission	
standards and is available to ADSM-N & Puerto Rico dealers.	
SHELL KIT, SQR, PADFOOT, FLD	416-1351
ANE 3 ORDER	0P-9003
ENGINE, CAT C4.4	629-8332
FUEL SYSTEM, DOOR	577-7672
LIGHTS, LED, STANDARD	648-9429
PLATFORM, ROPS/FOPS	648-6368
SEAT, VINYL	356-1226

DESCRIPTION	REF.#
SEAT BELT, 2"	590-3401
PRODUCT LINK, CELLULAR PL641	454-5454
INSTALLATION, ROPS/FOPS	454-0250
SENSOR, DRIVE POWER (MDP)	441-6675
TIRES, 23.1-26 8PR R-3	203-4717
FREQUENCY, VARIABLE	355-3546
SCRAPER, SHELL KIT READY	472-2057
NO BLADE	357-6261
OIL, HYD, STANDARD	362-4940
FUEL ANTIFREEZE, -25C (-13F)	0P-3978
PROTECTION, CYLINDER ROD	0P-3940
STORAGE PROTECTION	0P-4782
INSTRUCTIONS, ANSI	599-6402
INSTRUCTIONS, ANSI	648-7051
SERIALIZED TECHNICAL MEDIA KIT	421-8926
FILM GP "MADE IN BRAZIL"	554-1057
LIGHTING, WARNING	355-3059
MIRRORS, REARVIEW, EXTERNAL	354-5413
GUARD, TRANSMISSION	355-2660
ROLL ON-ROLL OFF	0P-4505

#### **STANDARD EQUIPMENT**

#### **POWERTRAIN**

CAT C4.4 turbo- charged diesel engine

with glow-plug

heater

Dual element air cleaner

Fuel filter/water separator/electronic

priming pump and water indicator

Three-speed throttle switch including

**ELECTRICAL** 

24-volt starting and charging system

alternator

(2) Maintenance free batteries -

750 CCA

Halogen working lights - canopy mounted

**ECOMODE** 

Dual propel pumps - 1 for drum and

1 for tires

Dual braking systems (service &

parking, drum only)

Two-speed hydrostatic transmission

Limited slip differential

(2 front-facing and 2 rear-facing)

Backup alarm and forward warning horn

Product link ready Beacon ready

**OPERATOR ENVIRONMENT** 

ROPS/FOPS platform

Four heavy-duty isolation mounts

Platform handrails/guardrails

Power steering

Adjustable tilt-steering column

Adjustable, rotating suspension seat

Rear view camera with display

Retractable seat belt

-engine oil pressure gauge

-engine coolant temperature gauge

-alternator charge

-fuel level gauge

-service hour meter

-engine RPM

-ground speed, vibe speed

-fuel rate gauge

Page 2

Adjustable, padded arm rest for propel lever operation On-board display with audible warning alarm and interface for: -hydraulic oil temperature gauge -engine load gauge -basic compaction measurement Lockable, vandalism guard for on-board display

12-volt power point

#### **COOLING**

Premixed 50% concentration of extended life coolant with freeze protection

to -37C (-35F)

#### **DRUMS**

Smooth drum 2134 mm (84") wide x 1534 mm (60.4") diameter

Dual amplitude with single frequency

Dual, pod-style eccentric weight

housings

Front adjustable steel scraper

## OTHER STANDARD EQUIPMENT

Locking composite engine enclosure Sealed-for-life hitch bearings Sight gauges: -coolant level -hydraulic oil level

Hydraulic tank locking cap Articulated frame with safety lock Transport tie-down and lift points

Fuel tank with lockable cap Quick connect hydraulic pressure test ports SOS ports: -engine -hydraulic -coolant

Universal bumper