

-- Standard Features --

-- Custom Options --



Kubota

S Series

SVL97-3HFCC

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Final Tier 4 Certified Kubota
Diesel Engine
Electronic Travel Torque
Management System
Vertical Lift Path Loader Frame
Standard Front Quick Coupler,
Float Standard
Hydraulic Quick Coupler Option
Loader Arm Self-Leveling
Loader Boom Lock
Open ROPS/FOPS
Optional enclosed and
pressurized cab with A/C
High Back, Adjustable, Vinyl,
Suspension Seat
Heated, Air Suspension Seat
Standard on Cab Models
2" Retractable Seat Belt And 2-
Piece Seat Bar
12V Electric Outlet
23.1 gpm Auxiliary Hydraulics
Standard, 41.2 gpm Option
Case Drain Line
Rigid Mounted Undercarriage, 5
Lower Track Rollers
High Grip Rubber Tracks, 17.7"
Standard
Two Speed Travel System
Automatic Wet Disk Parking
Brake
Kubota 4 Hydraulic Pump Load
Sensing System
2 Variable Displacement
Pumps
KubotaNOW Telematics
Standard
Lockable DEF Cap Guard
Hydraulic Joystick Controls
ISO Operating Pattern
Dial Knob and Foot Throttle
Controls
Decelerator Pedal
Stall Guard Engine Controls
Automatic Glow Plugs
7" Multifunction Touch Screen
Integrated Rear Camera
Keyless Start
Key Switch Stop System
Self Bleed Fuel System
2 Front and 2 Rear Working
Lights
Hour Meter, Engine Temperatur,
DEF, and Fuel Gauges and
Warning Lights
Horn and Backup Alarm
Lockable Fuel Cap

BASIC UNITS

SVL97-3HFCC, 17.7" Rubber
Tracks,
Open ROPS/FOPS Cab w/ Cold-
weather CCV Package,
Hydraulic Quick Coupler, Flow
Auxiliary Hydraulics, KSR

OPERATIONAL

DIMENSIONS

Operating Weight* 17.7" Rubber
Tracks, Open ROPS/FOPS Cab,
Mechanical Quick Coupler
11,676 lbs.
Rated Operating Capacity (ROC)
@ 35%
of Tipping Load complies with ISO
14397-1
and SAE J 818) 3,511 lbs.
Rated Operating Capacity (ROC)
@ 50%
of Tipping Load 4,850 lbs.
Tipping Load 9,700 lbs.
Auxiliary Hydraulics Flow 23.1/
41.2 gpm
Travel Speed (Low / High) 5.5 /
8.4 mph
Reach @ Maximum Height 40.7"
Height to Hinge Pin 128.6"
Ground Pressure 4.5 psi.

* Includes operator's weight, 175
lbs.

ENGINE

V3800-Tier 4 Kubota Final Tier 4
Diesel Engine
4 Cylinder, 4 Cycle, Turbo Charged
96.4 Gross HP @ 2400 rpm

DIMENSIONS

Cab Height 83.1"
Width (without attachment) 77.2"
Length (without attachment) 123.7"
Length of Track on Ground 65.6"

SVL97-3HFCC Base Price: \$105,522.00

Selected Kubota Attachments

(1) 80" HVY DUTY/LW PRF/LONG FLR/C. EDGE PNF AP-HD80LLC-80" HVY DUTY/LW PRF/LONG FLR/C. EDGE PNF	\$2,718.00
(1) SPECIAL APPL DOOR KIT CLOSED CAB S6861-SPECIAL APPL DOOR KIT CLOSED CAB	\$4,048.00
(1) HOSE STAY FOR SSV/SVL MODELS S6763-HOSE STAY FOR SSV/SVL MODELS	\$119.00
Total Kubota Attachments:	\$6,885.00
Total Attachments:	\$6,885.00
Configured Price:	\$112,407.00
Sourcewell Discounts:	
Kubota Items:	(\$26,977.68)
Total Discount:	(\$26,977.68)
SUBTOTAL:	\$85,429.32
2Yr SVL97-3HFCC Extended Warranty	\$3,150.00
Kubota Item Fees:	
Dealer Assembly:	\$18.33
Freight Cost:	\$831.25
PDI:	\$400.00
Hydraulic Cooler	\$10,950.00
FAE FA2973 MULCHER	\$37,700.00

Total Unit Price: \$138,478.90

Quantity Ordered: 1

Final Sales Price: \$138,478.90

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting
dealer

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.